

Survey of Section 31 T. 7 R. 46



FIELD NOTES.

Witness Trees	Inches in Diameter	Bearings	Distances in Links	Witness Trees	Inches in Diameter	Bearings	Distances in Links
2		$\frac{1}{2}$ distance bet N.E. cor. & E. $\frac{1}{2}$ m.p.					
Beech	11	N 11 $\frac{1}{2}$ ° W	31 $\frac{1}{2}$				
Oak	12	S 10° W	29 $\frac{1}{2}$				
		2 $\frac{1}{2}$ m.p. at on solid ledge of stone					
7		N 32 $\frac{1}{2}$ ° W	4 $\frac{1}{2}$				
Oak	6	N 70° W	18				
Oak	3	S 32° E	22				
		$\frac{1}{2}$ distance bet S.E. cor. & E. $\frac{1}{2}$ m.p.					
8		N 76° E	14				
Oak	14	S 76° W	13				
		Section corner of section 31, T 82					
9		S 46 $\frac{1}{2}$ ° E	23				
Oak	12	N 79° W	36				
		center of the S.E. quarter					
13		N 77° E	4				
Oak	24	S 18° E	28				
		$\frac{1}{2}$ distance between E. $\frac{1}{2}$ m.p. & center					
11		S 40° W	43				
Aspen	2	N 11 $\frac{1}{2}$ ° W	13				
		center of the N.E. quarter					
12		S 43° E	51				
Walnut	12	70° W	39				

Survey of Section 34 T. 7 R. 4 E



FIELD NOTES.

Witness Trees	Inches in Diameter	Bearings	Distances in Links	Witness Trees	Inches in Diameter	Bearings	Distances in Links
1/2 distance between N.W. corner & 1/2 m p.							
20 Oak	12	N 47° W	44 1/2				
21 Hickory	12	N 86° E	64 1/2				
1 1/2 m p perpendicular							
22 Oak	12	N 22° W	11				
23 Oak	2	S 66 1/2° W	17				
1/2 distance bet. N. 1/2 m p & center							
24 Walnut	4	S 31 1/2° W	8				
25 Walnut	3	N 63 1/2° W	28				
36 rods east of the N.W. corner							
26 Walnut	24	S 86 1/2° E	178				
36 rods east of the N.W. corner							
27 Oak	24	N 77 1/2° E	79 1/4				
36 rods southeasterly from a point 4 rods S of a point 36 rods east of the N.W. corner							
28 Oak	6	S 22° W	28				
29 Elm	2	N 1° W	27				

